

EXTREME protection DECKING OIL

- Water repellent barrier for exotic and autoclaved woods
- High concentration of anti-UV : blocks graying
- Marine protection: resistant to chlorinated water and stains

**PROTECTION
LONGUE
DURÉE**



Applicable à la
brosse sans essuyage

Compatible
bois neufs
et anciens



- Aspect: MATT
- Sizes : 1L – 2.5L – 5L
- Coverage : 1L = ± 10 sqm

INFORMATION



DRYING TIME

RECOAT 2h FULLY DRY 24h

TOOLS
BRUSH, ROLLER

TOOL CLEANING
WATER + SOAP

COVERAGE
+25 sqm in 2 COATS

1 pot = 25 sqm decks

ROLLER OR BRUSH EASY APPLICATION WITHOUT WIPING



BEFORE



AFTER

PURPOSE

- Particularly recommended for a durable and effective protection of floors and gratings in teak, exotic wood or pine, subjected to external aggressions (humidity, UV, chlorinated water ...): terraces of chalet or house by the sea, swimming pool tower ... Compatible with wood treated in an autoclave.

PERFORMANCES

- The Extreme Protection Decking Oil is formulated with natural oil and special "marine atmosphere" alkyd resin. It does not flake and provides lasting protection from the sun because it combines two types of anti-UV agents: a surfactant which protects the film from the Decking oil, and an agent which penetrates deeper into the wood. Very rich in water-repellent agents, it durably waterproofs wood against rainwater, chlorinated water, humidity and protects against stains and grease. Microporous, it lets the wood breathe. It preserves contact with wood and its natural matt appearance. Formulated in aqueous phase, it dries quickly and without annoying odor.

PREPARATION

The wood must be bare, clean and dry.

- OLD WOOD: carry out a preliminary cleaning with V33 Decking Cleaner.
- OILY WOOD: it is preferable to let the wood age a little in exterior so that the support is degreased before applying the Decking oil.

V33 TIPS

Ideal application conditions: between 12°C and 25°C in dry weather. On new or bare wood, treat if necessary with the V33 Treatment for Exterior Woodwork. In the event of localized stains, clean using the V33 Decking Cleaner. The appearance may vary depending on the wood species. Try it out first. For routine maintenance, a simple cleaning with water is sufficient.

APPLICATION

Milky appearance in a pot which disappears after drying. 1st application : Stir well with a stick before and during use. Liberally apply the first coat of Decking oil in the direction of the wood fibers, with a brush, a flat brush or a roller with short hair (12mm) so as to impregnate the wood well but without leaving any extra thickness. Leave to penetrate for 2 hours. Directly apply a second coat without wiping, smoothing the excess product with a brush to avoid streaks and highlights. Wait 24 hours for complete drying. CAUTION: Risk of self combustion. Wet textiles and tools soiled by the product with water and dispose of them in a container tightly closed. Clean tools with soapy water.

CARE

On worn areas, as soon as the wood turns white or dull, apply 1 to 2 coats of Decking oil in the same way. The connections are invisible. The Extreme Protection Decking oil does not flake, so it does not require sanding or stripping before maintenance.



NATURAL



TEAK