



HIGH PROTECTION WOODSTAIN Collection AUTHENTIC

- High resistance resin to wood variations
- Anti stain texture



DESTINATION

For all exterior and interior woodwork: cladding, shutters, gates, fences, windows, beams...

- On all types of new and old European and exotic woods: oak, softwood, larch, douglas, red cedar ...
- Compatible with all types of previously applied woodstains.

PREPARATION

The wood to be stained must be clean, dry, healthy and not greasy. Sand the corners and edges to round them slightly.

- RAW WOOD: sand with sandpaper to obtain a smooth surface and remove dust. Pre-treat your wood with the V33 universal treatment
- BARE DIFFICULT WOOD (OAK, CHESTNUT, LARCH, RED CEDAR, DOUGLAS, EXOTIC WOODS ...): dilute the first layer with 15% water and apply a second layer undiluted (avoid a greasy application). On greasy wood, degrease with a solvent cleaner.
- ALREADY STAINED WOODS: brush to remove non-adhering parts. Sand with sandpaper to obtain a smooth surface and remove dust.

HOW TO APPLY

Ideal application conditions: between 12 and 25°C in dry weather and without draft.

- Stir well the stain before and during use with a long and large stick.
- Apply with 2 coats with a brush, a roller or a spray gun (10% dilution).

V33 ADVICE

On new or heavy exposed wood, it is recommended to apply a third coat as when using the lighter shades.

- The clear shade is recommended for interior use only.
- For an exterior use, the clear may be used to dilute the tones other shades.

PROTECTION

The 8 year duration concerns:

- new or to renovate woods from common species: in accordance with the method of preparation and application.
- on vertical woodwork only. South and South-West exposure: apply 3 layers.

The guarantee is limited to reimbursement of the product (on presentation of the bottle and the receipt) and covers only the appearance of the woodstain.

SAFETY RECOMMENDATIONS and PRECAUTIONS FOR USE

Contains biocidal products: contains C(M)IT/MIT (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. Close the container after use. EU limit value for this product (Category A/e - Interior/exterior trim varnishes and woodstains, including opaque woodstains): 130g/l (2010). This product contains max 4g/L VOC.



Aspect: satin

Sizes: 0.75L, 2.5L

DRYING TIME

3H between coats
12H complete drying time

Coverage in 1 coat, per L: 12m²

Cleaning: Water

Tools: brush, roller, spray gun