



AQUAGEL WOODSTAIN

- *High resistance to UV and weather conditions*
- *Quick drying*



DESTINATION

- For all interior and exterior vertical woodwork: shutters, gates, fences, windows, garden houses ...
- On all types of new and old European and exotic woods
- Compatible with all types of previously applied woodstains
- Microporous anti-UV formulation : lets the wood breathe by protecting it from UV.

PROPERTIES

- Total beading effect that blocks water and moisture on the surface, thanks to the AQUASTOP Technology.

PREPARATION

The wood to be stained must be clean, dry, healthy and not greasy. Sand the corners and edges to round them slightly.

- **RAW WOOD:** sand with sandpaper to obtain a smooth surface and remove dust. Pretreat your wood with the V33 multi purpose treatment
- **ALREADY STAINED WOODS:** brush to remove non-adhering parts. Sand with sandpaper to obtain a smooth surface and remove dust.
- **BARE DIFFICULT WOOD (OAK, CHESTNUT, LARCH, RED CEDAR, DOUGLAS, EXOTIC WOODS ...):** dilute the first layer with 15% water and apply a second layer undiluted (avoid a greasy application). On greasy wood, degrease with a solvent cleaner.

HOW TO APPLY

Ideal application conditions: between 12 and 25°C in dry weather and without draft.

- Stir well the stain before and during use with a long and large stick .
- Apply with 2 coats with a brush, a roller or a spray gun (10% dilution).

Be careful: the colour in the tin does not correspond with the final colour/shade.

On new or heavy exposed woods, it is recommended to apply a third coat as far as the lighter colours/shades are concerned. The clear shade is recommended for an interior use.

For exterior use, use this shade only to dilute other shades.

V33 ADVICE

- The obtained colour/shade depends on the initial colour of the wood and of its age. The older the wood, the darker the result.
- In order to preserve the remaining product, empty contents into a smaller container (no air).



Aspect: satin

Sizes: 0.75L, 2.5L

DRYING TIME

3H between coats

12H complete drying time

Coverage in 1 coat, per L: 12m²

Cleaning: Water

Tools: brush, roller, spray gun



PROTECTION

The 6 years duration concerns:

- new or to renovate woods from common species: in accordance with the method of preparation and application.
- on vertical woodwork only. South and South-West exposure: apply 3 layers.

The guarantee is limited to reimbursement of the product (on presentation of the bottle and the receipt) and covers only the appearance of the woodstain. The 6 years duration depends on the exposure and on the weather conditions. This period may be reduced in the event of severe weather conditions or of surfaces in constant exposure with moisture when the water can not run.

SAFETY RECOMMENDATIONS and PRECAUTIONS FOR USE

Contains biocidal products (preservatives): contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. EUH211 : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. Close the container after use. EU limit value for this product (Category A/e - Interior/exterior trim varnishes and woodstains, including opaque woodstains): 130g/l (2010). This product contains max 4g/L VOC.